
CAT 6 Solid/Stranded 8P8C RJ-45 Shielded Modular Plug

PRODUCT SPECIFICATION

Package includes:

A. CAT 6 8P8C Shielded Modular Plug, 100 pcs
B. Loading Bar, 100 pcs




Features and Benefits:

- Designed for CAT 6, 8-position 8-conductor, solid or stranded wires
- Ideal for customization of cords for voice or high speed data applications
- Accepts 24~23 AWG solid or stranded
- Used with ICACSCT864 and ICACSCT845 crimping tools
- UL recognized


PLUG,CAT 6,SOLID/STRANDED,SHIELDED,100PK			
ITEM NO.	ICMP8P8C6S	REV.	A
DWG NO.	PSMP8P8C6S	PAGE NO.	1

ICC PremiumProducts ProvenPerformance CompetitivePrices

CUSTOMER CARE / TECHNICAL SUPPORT * CSR@ICC.COM / 888-ASK-4-ICC (275-4422) * 14700 Alondra Blvd., La Mirada, CA 90638 * www.icc.com



LOADING BAR



NOTE: UNLESS OTHERWISE SPECIFIED

1. ELECTRICAL:
   - A. CURRENT/VOLTAGE RATING: 1.5 AMPS / 30 VAC 42 VDC
   - B. CONTACT RESISTANCE: 10 MILLIOHMS MAX.
2. PERFORMANCE:
   - A. MEETS OR EXCEEDS CATEGORY 6 EIA/TIA 568 A-B.2
   - B. INSERTION/EXTRACTION LIFE: 1000 CYCLES
   - C. ROHS COMPLIANT
3. OPERATION TEMPERATURE: -40°C ~ +85°C
4. MATERIAL & FINISH:
   - A. HOUSING: POLYCARBONATE, UL 94V-0
   - B. CONTACT: PHOSPHOR BRONZE, .012 THICK
   - C. GOLD PLATING: STANDARD PLATING IS 1.27 MICRON/50 MICRO INCH GOLD OVER 100 MICRO INCH NICKEL
   - D. SHIELD:
     - -MATERIAL: .012 THICK CDA-260, 1/4 HARD BRASS
     - -PLATING: 100-150 MICRO-INCH TIN PLATED, 100% TIN
   - E. LOADING BAR:
     - -COLOR: BLACK
     - -MAXIMUM STRANDED/SOLID CONDUCTOR DIAMETER: 0.042"

PLUG,CAT 6,SOLID/STRANDED,SHIELDED,100PK			
ITEM NO.	ICMP8P8C6S	REV.	A
DWG NO.	PSMP8P8C6S	PAGE NO.	2

ICC
Premium**Products**
Proven**Performance**
Competitive**Prices**

CUSTOMER CARE / TECHNICAL SUPPORT * CSR@ICC.COM / 888-ASK-4-ICC (275-4422) * 14700 Alondra Blvd., La Mirada, CA 90638 * www.icc.com